



LOADED FITMENT GUIDE

ISUZU D-MAX

2012 - CURRENT



GUNBARREL 1675kg Load-Rated



GREY/BLACK LIP

SATIN BLACK

MACHINED

Part No.	Finish	Rim	Width	PCD	Offset	Flares*
22063SG	GREY/BLACK LIP	17	9	6/139.7	18P	
22063MS	MACHINED	17	9	6/139.7	18P	
22063SB	SATIN BLACK	17	9	6/139.7	18P	
22863SG	GREY/BLACK LIP	18	9	6/139.7	18P	
22863MS	MACHINED	18	9	6/139.7	18P	
22863SB	SATIN BLACK	18	9	6/139.7	18P	

STOCKTON 1675kg Load-Rated



MACHINED/BLACK LIP

BRONZE/BLACK LIP

GREY/BLACK LIP

SATIN BLACK

MACHINED

Part No.	Finish	Rim	Width	PCD	Offset	Flares*
21761SG	GREY/BLACK LIP	17	8.5	6/139.7	5P	•
21761MS	MACHINED	17	8.5	6/139.7	5P	•
21761SB	SATIN BLACK	17	8.5	6/139.7	5P	•
21761BB	BRONZE/BLACK LIP	17	8.5	6/139.7	5P	•
21063SG	GREY/BLACK LIP	17	9	6/139.7	18P	
21063MS	MACHINED	17	9	6/139.7	18P	
21063SB	SATIN BLACK	17	9	6/139.7	18P	

Part No.	Finish	Rim	Width	PCD	Offset	Flares*
21063SS	MACHINED/BLACK LIP	17	9	6/139.7	18P	
21063BB	BRONZE/BLACK LIP	17	9	6/139.7	18P	
21863SG	GREY/BLACK LIP	18	9	6/139.7	18P	
21863MS	MACHINED	18	9	6/139.7	18P	
21863SB	SATIN BLACK	18	9	6/139.7	18P	
21863BB	BRONZE/BLACK LIP	18	9	6/139.7	18P	

* - this size may require flares, use only as a guide.

